

Granville Rapid Cool Red Antifreeze

1 Litre, 2 Litre, 5 Litre, 20 Litre & 200 Litre

PRODUCT DESCRIPTION

Granville Rapid Cool Red Antifreeze and Coolant is an ethylene glycol based engine coolant concentrate, which uses Organic Acid Inhibitor Technology (OAT) and is free from nitrates, amines, phosphates, borates and silicates. Granville Rapid Cool has a 5 year or 250,000km life and should be changed whichever is the sooner. Unlike traditional coolants which employ inorganic inhibitors, Rapid Cool Red has excellent hard water stability and very low inhibitor depletion rates.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

BS: 6580:2010
Chrysler: MS 9176
Ford: WSS-M97B44-D
GM: 6277M
MAN: 324 SNF
MB: 325.3
Renault: 41-01-001
VW: TL 774 D & TL 774 F

PRODUCT BENEFITS

- * 5 year protection
- * Organic Acid Technology
- * Ethylene Glycol based
- * BS6580 : 2010

DIRECTIONS FOR USE

As recommended by the engine manufacturer.



* Image for illustrative purposes only.

| SIZE | PART NO | BARCODE |
|-----------|---------|---------------|
| 1 Litre | 1019 | 5020618010197 |
| 2 Litre | 1020 | 5020618010203 |
| 5 Litre | 1021 | 5020618010210 |
| 20 Litre | 1022 | 5020618010227 |
| 200 Litre | 1023 | 5020618010234 |



Granville Rapid Cool Red Antifreeze

1 Litre, 2 Litre, 5 Litre, 20 Litre & 200 Litre

DOSAGE INFORMATION

For normal use (-12°C freeze protection) dilute 1 part Antifreeze to 2 parts water.

For optimum protection down to -22°C, use 50% product (1 part Antifreeze to 1 part water).

STORAGE INSTRUCTIONS

Store sealed in a cool dry place.

SHELF LIFE

3 years from date of manufacture.

SPECIFICATION INFORMATION

Complies with:

BS 6580 (2010); VW VAG TL 774 D&F; FORD WSS-M97B44-D; MB 325.3; RENAULT 41-01-001; CHRYSLER MS9176; GM 6277M; MAN 324 SNF.VW G12 & G 12+

| | | |
|-------------------|---|-------------------|
| Appearance | : | Pink/Red liquid |
| Odour | : | Odourless |
| Solubility | : | Miscible in water |

| Test | Method | Unit | Min. | Max. | Typical |
|----------------|--------|------|------|------|---------|
| Freezing Point | | °c | | -22 | |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

